PROJECT	DESIGNATION
PB-19-0006	
CONTRACT	STRUCTURE NUMBER
	33016 33017

DATE: 06/28/2021

President

Member

Auditor


County Highway Engineer


Vice President


HAMILTON COUNTY HIGHWAY DEPARTMENT

REPLACEMENT PLANS FOR SMALL STRUCTURE NO. 33016 AND NO. 33017

256TH STREET OVER DEER CREEK
WHITE RIVER TOWNSHIP
HAMILTON COUNTY, INDIANA
PB-19-0006







ATITUDE: 40°09'43" N	LONGITUDE: 85°56'34" W

GROSS LENGTH:	0.055	MI.
NET LENGTH:	0.055	MI.
MAX. GRADE:	0.72	<u></u> %

INDIANA DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS DATED 2020 TO BE USED WITH THESE PLANS.



Hanson Professional Services Inc. 6510 Telecom Drive, Suite 210 Indianapolis, Indiana 46278 Phone: (317)293-9024



PLANS PREPARED BY:	HANSON PROFESSIONAL SERVICES INC.	(317)293-9024 PHONE NUMBER
CERTIFIED BY:	Robert J. Zolcak	<i>6/28/2021</i> DATE

APPROVED BY:

Steve Dillinger

Robin M Mills

Robin Mills

HAMILTON COUNTY

BOARD OF COMMISSIONERS

POWER: Duke Energy Indiana, LLC 1619 W. Defenbaugh Kokomo, IN 46902 Contact: Tim Umbaugh Phone: (317)736-2018 TELECOMM: Frontier Communications of Indiana 221 W. Washington Street

Fairmount, IN 46928

Contact: Dan White


Phone: (765)436-2206

	REVISIONS			
SHEET NO.	DATE	REVISED		


	SHEET INDEX			
SHEET NO.	SUBJECT			
1	TITLE			
2	INDEX OF SHEETS & UTILITY CONTACTS			
3	TYPICAL SECTIONS			
4 - 5	LOCATION CONTROL ROUTE SURVEY PLAT			
6	PLAT NO. 1			
7	MAINTENANCE OF TRAFFIC (DETOUR ROUTE)			
8	PLAN AND PROFILE			
9 - 10	EROSION CONTROL AND DEWATERING			
11	SOIL BORINGS			
12	LAYOUT			
13	GENERAL PLAN			
14	PAVEMENT MARKING PLAN			
15	SUMMARY TABLES			
16 - 23	CROSS SECTIONS			




J. JOHNHAM	RECOMMENDED FOR APPROVAL	Robert J. Jolcak 6/28/2021 DESIGN ENGINEER DATE	HAMILTON COUNTY HIGHWAY DEPARTMENT	SCALE NO SCALE	STRUCTURE NUMBER 33016 33017 DESIGNATION	
OIANA CHOMINITALIS	DESIGNED: RJZ CHECKED: RMM	DRAWN: ESC CHECKED: RJZ	INDEX OF SHEETS AND UTILITY CONTACTS	SURVEY BOOK CONTRACT	SHEETS 2	



ATE REVISION					STRUCTURE NUMBER
	MIL NEW DECOMMENDED A	R M MO A M HAMILTON COUNTY		33016 33017	
	RECOMMENDED FOR APPROVAL	// when, J. 6/28/2021	HIGHWAY DEPARTMENT	SCALE	DESIGNATION
	No. DESIGN E	ENGINEER DATE		1/4" = 1'-0"	
	19700379 * DESIGNED: RMM	DRAWN FOO		SURVEY BOOK	SHEETS
	DESIGNED: RMM	DESIGNED: RMM DRAWN: ESC	ROADWAY		3 of 23
			TYPICAL SECTIONS	CONTRACT	PROJECT
	CHECKED: RJZ	_ CHECKED: RMM			PB-19-0006





SURVEYOR'S REPORT

ROUTE SURVEY FOR 256TH STREET OVER DEER CREEK STRUCTURE NO. 33016 & 33017 HAMILTON COUNTY, INDIANA

GENERAL

In accordance with Title 865, Article 1, Chapter 12 of the Indiana Administrative Code ("Rule 12"), the following observations and opinions are submitted regarding the various uncertainties in the location of the lines and corners established this survey as a result of uncertainties in reference monumentation; in record descriptions and plats; in lines of occupation; and as introduced by random errors in measurement ("Relative Positional Accuracy").

- All monument reference ties are shown on the route survey plat.
- Should additional USPLS Corners be needed where none were found, they should be reestablished and tied into this survey.
- Item numbers are actual field survey point numbers used for control and topography.

Field measurements for this survey were in accordance with the specifications outlined in 865 IAC 1-12. Measurements are shown to the nearest 0.01 feet. Coordinates are shown to the nearest 0.0001 feet, not to indicate the precision of the work, but to allow for closure and adjustment by others if desired. All measurements, dimensions and coordinates are shown in U.S. Survey feet unless otherwise noted.

The purpose of this survey is to collect pertinent survey data for the replacement of Structure #33016 and the removal of Structure #33017 located along 256th Street within Hamilton County, IN. Throughout the structures, there is surface rust and minor deflection under the road. This project consists of the replacement of Structure #33016 with a new concrete box structure and Structure #33017 will be removed and not replaced.

Line "A" will now provide a basis for describing any new right-of-way that may be required as a result of this project.

THIS SURVEY IS NOT A PROPERTY RETRACEMENT SURVEY, ANY APPARENT PROPERTY LINES, CORNERS, SUBDIVISIONS OR SECTION CORNERS ARE BASED ON PHYSICAL EVIDENCE OR TESTIMONY.

HORIZONTAL CONTROL

The coordinates shown on the monuments are State Plane Coordinates, Indiana East, NAD 83 in U.S. Survey Feet or as otherwise noted. The primary Horizontal Control and Bearing Basis for this survey were developed by Trimble VRS RTK observations on all Control Points. The datum for these points is based upon State Plane Coordinates, Indiana East Zone (NAD83), Geoid 18B.

SCALE FACTOR: 0.9999666667

PROJECTION TYPE: TRAVERSE MERCATOR
ORIGIN LATITUDE: N 37° 30′ 00″

ORIGIN LONGITUDE: W 85° 40′ 00″

FALSE NORTHING: 820,208.333 U.S. FT.

FALSE EASTING: 328,083.333 U.S. FT.

The Relative Positional Accuracy (due to random errors in measurement) of this survey based on inverse distances of recovered section corners is within the specifications for a Urban Survey (0.07 feet, 21 millimeters) plus 50 parts per million, as defined in 865 IAC.

PRESENT STRUCTURE

The small structures are located on 256th Street, approximately 850 feet west of SR 213 in Hamilton County, Indiana. Structure 33016 carries 256th Street over Deer Creek and Structure 33017 carries 256th Street over UNT to Deer Creek. Both Structures are classified as "Functionally Obsolete" per the 2016 SIA reports.

ALIGNMENTS

Line "A" was established from the centerline of the existing roadway of 256th Street running through Structure Number 33016 per topographic survey. Line "A" bearing for this survey was determined to be North 89° 47' 14" East.

RECORD DESCRIPTIONS & FOUND MONUMENTATION

See the tables on sheet 1 for record instrument references and found monuments that were located as a part of this survey. In addition to any physical evidence found and shown herein, the descriptions from the referenced record instruments and the boundary surveys as shown on sheet 1 were used in placing the boundary lines associated with this project.

EXISTING RIGHT-OF-WAY

There was no evidence found for existing right-of-way along 256th Street; therefore, the existing edge of pavement will need to serve as the existing right-of-way for this project as shown on Sheet 1 of this Location Control Route Survey Plat.

SURVEY CONTROL MONUMENTS

- HPS1. Set 5/8" Iron Pin flush with ground at Sta. 12+79.31, 15.18' Lt. Line "A". Original monument; therefore, there is no uncertainty.
- HPS2. Set 5/8" Iron Pin flush with ground at Sta. 15+25.91, 18.17' Rt. Line "A". Original monument; therefore, there is no uncertainty.

LINE "A" CENTERLINE ALIGNMENT MONUMENTS

- 50. Calculated centerline point at P.O.T. Sta. 9+50.00, 0.00' Rt. Line "A". No Monument Set; therefore, there is no uncertainty.
- 51. Calculated centerline point at P.O.T. Sta. 16+50.00, 0.00' Rt. Line "A". No Monument Set; therefore, there is no uncertainty.

SECTION REFERENCE MONUMENTS

- 115. Found Mag Nail at the North Quarter Corner of Section 27, Township 20 North, Range 5 East, per the Hamilton County Surveyor Tie for this corner. The uncertainty in this monument as a section corner is estimated to be +/- 0.2 feet.
- Found Harrison Monument at the Northeast Corner of Section 27, Township 20 North, Range 5 East, per the Hamilton County Surveyor Tie for this corner. The uncertainty in this monument as a section corner is estimated to be +/-0.1 feet.
- 401. Found Mag Nail at the Northwest Corner of the Northeast Quarter of Section 26, Township 20 North, Range 5 East, as per county ties. The Hamilton County Surveyor Tie indicates an Iron Pin. The uncertainty in this monument as a section corner is estimated to be +/- 0.1 feet.
- 402. Found Harrison Monument at the Northeast Corner of Section 28, Township 20 North, Range 5 East, as per county ties. The uncertainty in this monument as a section corner is estimated to be \pm -- 0.1 feet.
- Found Harrison Monument at the Northwest Corner of the Northeast Quarter of Section 28, Township 20 North, Range 5 East, as per county ties. The uncertainty in this monument as a section corner is estimated to be +/- 0.2 feet.

- 404. Found Harrison Monument at the Northeast Corner of Section 33, Township 20 North, Range 5 East, as per county ties. The uncertainty in this monument as a section corner is estimated to be \pm 1-0.1 feet.
- 405. Found Harrison Monument at the Northeast Corner of the Southeast Quarter of Section 28, Township 20 North, Range 5 East, as per county ties. The uncertainty in this monument as a section corner is estimated to be +/- 0.2 feet.
- 406. Found Mag Spike at the Northeast Corner of the Southeast Quarter of the Northeast Quarter of Section 28, Township 20 North, Range 5 East, as per county ties. The Hamilton County Surveyor Tie indicates a Mag Spike with washer. The uncertainty in this monument as a section corner is estimated to be +/- 0.1 feet.
- 407. Found Harrison Monument at the Northeast Corner of the Southeast Quarter of Section 21, Township 20 North, Range 5 East, as per county ties. The uncertainty in this monument as a section corner is estimated to be +/- 0.1 feet.
- Found Harrison Monument at the Northeast Corner Section 21, Township 20 North, Range 5 East, as per county ties. The uncertainty in this monument as a section corner is estimated to be +/- 0.1 feet.
- 409. Found Harrison Monument at the Northeast Corner of Section 22, Township 20 North, Range 5 East, as per county ties. The uncertainty in this monument as a section corner is estimated to be +/- 0.1 feet.
- 410. Found Mag Nail at the Northeast Corner of the Southeast Quarter of Section 22, Township 20 North, Range 5 East, as per county ties. The uncertainty in this monument as a section corner is estimated to be +/- 0.1 feet.
- 411. Found Harrison Monument at the Northeast Corner of the Southeast Quarter of Section 27, Township 20 North, Range 5 East, as per county ties. The uncertainty in this monument as a section corner is estimated to be +/- 0.1 feet.
- 412. Found Harrison Monument at the Northeast Corner of Section 34, Township 20 North, Range 5 East, as per county ties. The uncertainty in this monument as a section corner is estimated to be +/- 0.1 feet.
- 413. Found Harrison Monument at the Northwest Corner of the Northeast Quarter of Section 34, Township 20 North, Range 5 East, as per county ties. The uncertainty in this monument as a section corner is estimated to be +/- 0.1 feet.


RN					
	SURVEY STARTED				
	27 J <i>i</i>	ANUARY	2020]	
0 CAD 59PM W	SURVE	y comi	PLETED		
19 <u>L</u> 0210 20 4:59.	28 JANUARY 2020				
19JOBS 7 70, 20,	ROUTE PLAT SHEETS				
: 19. SEP 1	2	OF	2	$\ $	

PREPARED BY:




FIELD SURVEYOR'S STATEMENT


THIS SURVEY, TO THE BEST OF MY KNOWLEDGE AND BELIEF, IS EXECUTED ACCORDING TO THE PROVISIONS OF TITLE 865 I.A.C. 1-12-20 THROUGH I.A.C. 1-12-25 REGARDING ROUTE SURVEYS, EXCEPT THAT ANY DATA SHOWN REGARDING THE LOCATION OR DESCRIPTION OF THE EXISTING PARCELS IS NOT A PART OF THIS SURVEY.





I AFFIRM, UNDER THE PENALTIES FOR PERJUR HAVE TAKEN REASONABLE CARE TO REDACT EA SECURITY NUMBER IN THIS DOCUMENT, UNLESS BY LAW.	CH SOCIAL
PREPARED BY:	0 10 2020
	9 - 10 - 2020
REGISTERED LAND SURVEYOR, FIELD	DATE


LIABATI TONI COLINITY	HORIZONTAL SCALE	BRIDGE FILE		
HAMILTON COUNTY	NO SCALE			
HIGHWAY DEPARTMENT	COUNTY	DESIGNATION		
	HAMILTON COUNTY			
LOCATION CONTROL	SURVEY BOOK		SHEETS	
LOCATION CONTROL		5	of	23
ROUTE SURVEY PLAT	CONTRACT	PROJECT		
			DD 10 000C	




















NOTE:
See Plan and Profile and Layout
Sheets for Boring Locations.

RECOMMENDED 6/28/2021 FOR APPROVAL DESIGN ENGINEER DATE		HAMILTON COUNTY HIGHWAY DEPARTMENT	SCALE	STRUCTURE NUMBER 33016 33017 DESIGNATION	
			NO SCALE		
		COTI	SURVEY BOOK	SHEET	ΓS
DESIGNED:	DRAWN:	SOIL		11 of	23
CHECKED.	CLICKED.	BORINGS	CONTRACT	PROJE	СТ
CHECKED: CHECKED: DURINGS		DOMINGS		PB-19-0	006







SOIL PARAMETERS FOR WINGWA	ALLS
Factored Bearing Resistance (psf)	3700
Nominal Bearing Capacity (psf)	8300
Resistance Factor	0.45
Friction Angle of the Backfill	22°
Friction Factor of the Foundation Soil	N/A
Angle of Internal Friction of the Foundation Soil	N/A
Ultimate Adhesion between Foundation Soil and Poured Concrete Footing (Ca) psf	1100
Soil Cohesion (psf)	1625

GENERAL NOTES

Groundwater may be at a higher elevation than the invert and therefore, Dewatering could be required during the Excavation and Placement of the Drainage Structure.

DESIGN DATA

Designed for HL-93 Loading in accordance with the AASHTO LRFD Bridge Design Specifications 8th Edition, 2017 (LRFD 8).

Dead Load increased 35 psf for Future Wearing Surface.

GENERAL PLAN
PRECAST CONCRETE BOX
1 SPAN: 10'-0"
30'-0" CLEAR ROADWAY SKEW: 45° LT
256th STREET OVER DEER CREEK
HAMILTON COUNTY

DATE	REVISION

No PE19600434 STATE OF WOIANA WOLL	*

RECOMMENDED FOR APPROVAL	Robert DESIGN EN	GINEER	Jolcak	<i>6/28/2021</i> DATE	
DESIGNED: RJZ		DRAWN: I	ESC		
CHECKED: RMM		CHECKED): RJZ		


HAMILTON COUNTY HIGHWAY DEPARTMENT
GENERAL PLAN

256th STREET OVER DEER CREEK

	STRUCT	URE I	NUMBER
	3301	.6 33	3017
SCALE	DESI	GNA	ΓΙΟΝ
AS NOTED			
SURVEY BOOK	S	HEET	S
	13	of	23
CONTRACT	PF	ROJEC	T

PB-19-0006

I:\19jobs\19L0210\CAD\Struct\Sheet\Sht General Plan_01.dgn



														F	PAVEM	ENT C	TNAU	ITIES	S AND	APPR	COACH	TABLI	E														
LOCATION	DESCRIPTION (APPROACH TYPE OR CLASS)	WIDTH	LENGTH	RADII	NCE BEYOND R/W LINE		FACE R/W I	CONCRETE CONCRETE		GRAD			EXCA	VATION		A FOR A	APPROAC	CHES	SURFACE TYPE B		INTERMEDIATE WE DITTE TO TABLE BOTTE TO TABLE BOTTE BO	IALS	BASE TYPE B	GRADE TREATMENT TYPE ID	GRADE TREATMENT TYPE II	6" PCCP	9" PCCP	T ADHESIVE, ERMEDIATE	TERIAL DR: LACK COAT		COMPA AGGRE NO. 53,	EGATE	/	COMPA AGGRE FO SURF NO.	EGATE OR FACE	LING, ASPHALT, 1.5"	REMARKS
					STAI	MPA										LBS. P	ER SYD.	•		LB	S. PER S	YD.		SUB	SUB			JOIN			DEF	PTH		DEP	PTH	MIL	
					SIQ	8			1	2	3	4	CUT	FILL	165	275	880		165		330		660							6"	VAR.						
		FT	FT	FT	FT	SYS	SY	S SYS	8 %	%	%	%	CYS	CYS	TON	TON	TON	TON	TON	TON	TON	TON	TON	SYS	SYS	SYS	SYS	LFT	SYS	TON	TON	TON	TON	TON	TON	SYS	
LINE	"A"																																				
10+10 TO 16+00	MAINLINE												703	1301					146		294		594						3533	583	106						
10+75 LT	MOD. CLASS V	24	21.9	25					12.0)			3	1																29							
10+75 RT	MOD. CLASS V	24	18.3	25					9.8				1	3																25							
	TOTALS												707	1305					146		294		594						3533	637	106						

															ST	ruct	URE DA	ATA													
STRUCTURE	STATION	RIGHT OO CROSS	OFFSET	SIZE	DESCRIPTION MANHOLE, INLET, CATCH BASIN, OR SPECIALTY STRUCTURE AND TYPE	LENGTH	VIDEO INSPECTION LENGTH SKEW	FLOW UP STREA	DOW		SERVICE LIFE	pH	BACKFILL METHOD STRUCTURE BACKFILL	ТҮРЕ	STRUCTURE BACKFILL	TYPE	FLOWABLE BACKFILL	TYPE	GEOTEXTILES	REVETMENT RIPRAP	SUMP DEPTH	GEOTEXTILE, AND TYPE 1A	RIPRAP	CONCRETE,	VID INSPE(PIPE SECT	GRATED BOX END SECTION		SECTION	CONNECT	CULVERT ASSET ID	REMARKS
			FT	IN		LFT	LFT L	.FT ELEV	. ELEV	/. YF	S C)	CYS		CYS		CYS		SYS	TON	IN	SYS	TYPE TO	NS CY	S LFT EACH TY	YPE SLOPE EACH	I TYPE	SLOPE	EACH		
	LINE "A"																														
10	10+75.5		21.8	12	3	42	4.12L	0.5 822.8	5 822.4	7 5	0 NA	A 7	2 4.2	2							3				2						
																											1				

		P]		RIAL TAB	LE
		40	STRUCTU	RE NUMBER	1
DIDE TYPE / CHAPE		10			+
PIPE TYPE / SHAPE		12			
SMOOTH PIPE SIZE	7F	12			+
CORRUGATED PIPE SIZ	<u>1E</u>	77			
RCP/RCHEP (S) CLASS		II 1000			-
D 0.01 RATING	CC 2 (C)	1000			
NON-REINFORCED CONCRETE PIPE, CLA	55 3 (5)				
CORRUGATED PE PIPE, TYPE S (S)					
RIBBED PE PIPE (S)*	4 DD				-
SMOOTH WALL PEPIPE (S)* / MAXIMUM	I DR				
PROFILE WALL PVC PIPE (S)					+
SMOOTH WALL PVC PIPE (S)*	ц (C)				1
VITRIFIED CLAY PIPE, EXTRA STRENGTI	, ` <i>'</i>				+
FULLY BIT. PAVED & LINED (S)	CORR. PROFILE				
, ,	THICKNESS				
ZINC COATED (C)	CORR. PROFILE				_
	THICKNESS	2 2 (21) \ (4 (21)			
ZINC COATED W/ BPI (C)	CORR. PROFILE	2 2/3" X 1/2"			
ZINC COATED W/ BPI (C) ALUM. COATED TYPE 2 (C)	THICKNESS	0.064			
ALUM. COATED TYPE 2 (C)	CORR. PROFILE	2 2/3" X 1/2"			
	THICKNESS	0.064			
L ALUM. COATED TYPE 2 W/ BPI (C)	CORR. PROFILE				
	THICKNESS				
田 POLYMER PRECOATED GALVANIZED (C)	CORR. PROFILE	2 2/3" X 1/2"			
GALVANIZED (C)	THICKNESS	0.064			
핃 POLYMER PRECOATED	CORR. PROFILE				
POLYMER PRECOATED GALVANIZED W/ BPI (C) POLYMER PRECOATED GALVANIZED	THICKNESS				
POLYMER PRECOATED GALVANIZED CORRUGATED STEEL PIPE TYPE 1A (S) FIBER BONDED BITUMINOUS	CORR. PROFILE				
CORRUGATED STEEL PIPE TYPE 1A (S)	THICKNESS				
FIBER BONDED BITUMINOUS	CORR. PROFILE				
COATED (C)	THICKNESS				
FIBER BONDED BITUMINOUS	CORR. PROFILE				
COATED W/ BPI (C)	THICKNESS				
CORRUGATED ALUM. ALLOY PIPE (C)	CORR. PROFILE	2 2/3" X 1/2"			
CORROGATED ALOM: ALEOT FIFE (C)	THICKNESS	0.060			
CORRUGATED ALUM. ALLOY PIPE	CORR. PROFILE				
W/ BPI (C)	THICKNESS				
STR. PLATE ALUMINUM ALLOY	CORR. PROFILE				
PLATE (C)	THICKNESS				
STR. PLATE ALUMINUM ALLOY	CORR. PROFILE				
PLATE W/ CFP (C)	THICKNESS				
	CORR. PROFILE				
STR. PLATE STEEL PIPE (C)	THICKNESS**				
CTD DIATE CTEEL DYDE (CT	CORR. PROFILE				
STR. PLATE STEEL PIPE W/ CFP (C)	THICKNESS**				
				1	1
DATE	REVISIO)VI			

<u>LEGEND</u>

Reinforced Concrete Pipe RCHEP Reinforced Concrete Horizontal Elliptical Pipe Polyethylene Dimension Ratio

Polyvinyl Chloride BIT Bituminous
CORR Corrugation
BPI Bituminous P
ALUM Aluminum Corrugation Bituminous Paved Invert STR
CFP
CIR
DEF
(S)
(C)
OK
(LS) Structural

Concrete Field Paving Circular Pipe Deformed Pipe Smooth Pipe Material
Corrugated Pipe Material
Acceptable for Use
Lock Seam Pipe Required

Refer to Standard Drawings 715-PHCL-18 and 715-PHCL-19 for nominal diameter appropriate for pay item diameter.

Tabulated thickness refers to top and side plates. Bottom plates shall be of next greater available thickness.

				MONUMENT T	ABLE			
LOCATION	LEFT	CENTER	RIGHT	MONUMENT TYPE	TYPE "B" EACH	TYPE "C" EACH	TYPE "D" EACH	SECTION CORNER EACH
LINE "A"								
STA. 11+60		•			1			
STA. 14+50		•			1			
	TC)TAL	_S		2			


			MAILBOX APP	ROACH	IES							
STATION	FT	ìНТ	DESCRIPTION	WIDTH	ASS	SEMBLY REQ'D						
STATION	LEF	RIGHT	DESCRIPTION	(FT)	SINGLE	DOUBLE						
LINE "A"												
STA. 15+95			RESET		1							
STA. 15+99	•		RESET		1							
TC	TAL	_S			2							


R/W MARKER TABLE													
STATION	LINE	LEFT	RIGHT	OFFSET (FT)	EACH								
9+95.35	"A"			9.0	1								
9+95.22	"A"			25.0	1								
10+05.00	"A"			9.00	1								
10+05.00	"A"			25.0	1								
13+20.00	"A"		•	45.0	1								
13+35.00	"A"			65.0	1								
13+85.00	"A"			60.0	1								
14+27.01	"A"			50.0	1								
16+27.80	"A"			9.0	1								
16+27.99	"A"			20.0	1								
16+35.25	"A"			20.0	1								
16+35.34	"A"		•	9.0	1								
				TOTALS	12								


DATE	REVISION	


zarin.	M. MILNE	1111
W * PR	NO. 19700379 STATE OF	(* * J
THIN,	ONAL ENGL	

		HAMILTON COUNTY HIGHWAY DEPARTMENT	STRUCTURE NUMBER			
	$n \cdot n \cdot n$		33016 33017)17	
FOR APPROVAL /) 09 ///.	I when, J. 6/28/2021		SCALE	DESIGNATION		
DESIGN E			NO SCALE			
DEGLEVED DAMA	55 MAN 500	CLINANA A DV	SURVEY BOOK		SHEETS	
DESIGNED: RMM	DRAWN: ESC SU	SUMMARY		15	of	23
CHECKED- D17	CLIECKED, DAMA	TABLES	CONTRACT		PROJECT	•
CHECKED: RJZ	CHECKED: RMM	IADLLS			PB-19-000	16












RECOMMENDED FOR APPROVAL DE	6/28/2021 ESIGN ENGINEER DATE	INDIANA DEPARTMENT OF TRANSPORTATION	SCALE 1" = 5'	BRIDGE FILE 33016 33017 DESIGNATION
DESIGNED: RMM	DRAWN: RLH	CROSS SECTIONS	SURVEY BOOK	SHEETS 18 of 23
CHECKED: RJZ	CHECKED: RMM	LINE "A"	CONTRACT	PROJECT PB-19-0006

I:\19jobs\19L0210\CAD\Road\Model\RD_Cross Sections.dgn







RECOMMENDED			INDIANA DEPARTMENT OF TRANSPORTATION		BRIDGE FILE 33016 33017	
	FOR APPROVAL DESIGN ENGINEER			SCALE 1" = 5'	DESIGNATION	
			CD CCC CECTIONS	SURVEY BOOK	SHEETS	
	DESIGNED: RMM	DRAWN: RLH	CROSS SECTIONS		20 of 23	
	CHECKED: RJZ	CHECKED: RMM	LINE "A"	CONTRACT	PROJECT PB-19-0006	

I:\19jobs\19L0210\CAD\Road\Model\RD_Cross Sections.dgn

